

## HT-D-17



1. Conversion to the right voltage.
2. Stabilization of the voltage.
3. Compact size design.
4. Efficient cooling (thermal controlled fan).



### SPECIFICATION

Model No.:	HT-D-17
<b>INPUT SPECIFICATIONS</b>	
Nominal input voltage:	24V
Input range:	18~30VDC(±1V)
No load consumption:	0.03A(±0.5%)
<b>OUTPUT SPECIFICATIONS</b>	
Nominal voltage:	12.5V(±0.5V)
Voltage range:	12V~13V(±0.5V)
Ripple:	<1%
Maximum power:	25A(±1A)
Nominal power:	17A(±1A)
<b>PROTECTIONS</b>	
Over current:	yes
Over heat:	yes
<b>SAFETY&amp;EMC</b>	
EMC:	EN61000-6-4 : 2007, CISPR 11 : 2003 Class B, EN61000-6-2 : 2005, IEC 61000-4-2: 1995+A1:1998+A2: 2000, IEC61000-4-3: 2008, IEC61000-4-8: 1993+A1:2000.
LVD:	Compliance to EN60950
<b>GENERAL SPECIFICATIONS</b>	
Working temp.:	0~+40°C
Working humidity:	20%~90% RH non-condensing
Storage temp., humidity:	-30~+70°C/-22°F~+158°F, 10~95% RH
Temp.coefficientI:	±0.05%°C(0~55°C)
Efficiency:	>85%
Dimension(LxWxH):	178x89x50mm
Net weight:	0.6kgs